



**SALES:**

1195 S. DeAnza Blvd  
 San Jose, CA 95129  
 Off. 408.257.6345  
 Fax 408.257.3849

**PLANT:**

1895 San Felipe Rd  
 Hollister, CA 95023  
 Off. 831.637.9163  
 Fax 831.637.0756

[www.pacinterlock.com](http://www.pacinterlock.com)

**60 MM PAVERS and Fire Truck GVWR**

Using 60 mm pavers is an ideal solution to enhance the surrounding landscape while providing reliable and stable access for emergency vehicles. Pacific Interlock Pavingstone manufactures several 60mm paving stones, including textured stones, according to ASTM standard C-1319 that meet the compression test of 8000 psi in accordance with the testing procedures in ASTM C-42 and C-140.

When installed under normal soil conditions, the typical commercial installation of 60mm paving stones will have the following psi ratings if properly installed over a base of crushed stone that meets the ASTM D 2940 standards

<u>Depth</u>	<u>PSI rating</u>	<u>Lbs / SqFt</u>
4" depth	80 psi	11,520 psf
6" depth	120 psi	17,280 psf
10" depth	160 psi	23,040 psf

For vehicular traffic applications, the maximum recommended slope is 18% (about 10 degrees).

The Dept of Transportation code of regulations regarding Fire Trucks in Title 21; Div 2; Ch 7; Sec 1411.7 gives the following Axle weight configuration

<b>Axle Configuration</b>	<b>Max. allowable weight</b>
Single steering axle	23,000 pounds
Single tiller axle	24,000 pounds
Single drive axle	24,000 pounds
Tandem axles	48,000 pounds
Tridem axles	54,000 pounds

1) A two-axle aerial ladder fire truck and a two-axle aerial water tower fire truck shall not exceed 31,000 pounds on the rear axle. A three-axle aerial platform ladder fire truck shall not exceed 53,000 pounds on the tandem axle assembly. An aerial ladder fire truck, two-vehicle combination, shall not exceed 27,000 pounds on the single-drive axle of the power unit.

2) A pumper fire truck designed to carry a minimum capacity of 1,200 gallons shall not exceed 27,000 pounds on a single drive axle.

Allowing one square foot per tire the following GVWR per SqFt per tire would apply:

- Steering Axle: 11,500 psf per tire
- Single Tiller Axle 12,000 psf per tire
- Single drive axle: 12,000 psf per tire
- Tandem axles: 12,000 psf per tire
- Tridem axles: 9,000 psf per tire